

Features:

- Universal AC input
- RoHS compliance
- 3 - year warranty
- IP54 protection for damp environment
- Overvoltage protection
- Convection cooled
- Overcurrent protection
- Short circuit protection



Dimensions:155(L)x153(W)x59(H)mm

General Specifications

INPUT

Input voltage.....100~240VAC
 Input frequency47~400Hz
 Inrush current22A/110VAC
 (Cold start) 44A/220VAC




OUTPUT

Temp. Coefficient± 0.04% / °C
 Overvoltage protectionAutorecovery
 Over current protection Current limited
 Short circuit protection..... Autorecovery
 Transient response. .. (Load change 50% to 100%)
 Voltage deviation5%
 Recovery time2mS

EMC STANDARDS

EN 55011	Class B
EN 55022	Class B
EN 61000-4-2	Level 3
EN 61000-4-3	Level 3
EN 61000-4-4	Level 3
EN 61000-4-5	Level 3
EN 61000-4-6	Level 3
EN 61000-4-8	Level 3
EN 61000-4-11	Level 3

SAFETY STANDARDS

	EN 60950 (Marking)
	UL 60950 (Meet)
	CSA 22.2 (Meet)

ENVIRONMENTAL

Operating temperature: -20°C ~ 40°C ambient, derating each output at 2.5% per degree from 40°C to 60°C
 Operating humidity: Non-condensing, 5% ~ 95%RH.
 Vibration: Random vibration, 10Hz ~ 2KHz, 3axis.
 MTBF: 80,000hrs Min. Per MIL-HDBK-217F, 25°C GB.

Output Specifications

Model	O/P voltage Adjustment	Loading (A)			Ripple Noise	Line Reg.	Load Reg.	Efficiency	Overvoltage Protection
		Min.	Rated	Max.					
AE1150-12F	+12VDC -----	0A	12.5A	12.5A	100mVp-p	±1%	±2%	82%	15~17VDC
AE1150-24F	+24VDC -----	0A	6.3A	6.3A	150mVp-p	±1%	±1%	84%	27~30VDC
AE1150-48F	+48VDC -----	0A	3.1A	3.1A	250mVp-p	±1%	±1%	83%	52~56VDC

- NOTE:**
1. Each output can supply up to maximum current, but total loading can not exceed rated output wattage.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 110VAC input.
 4. Ripple & Noise is measured by using a 0.1uF/630V metalized capacitor & a 47uF electrolytic capacitor parallel on the test point, at rated load and 110VAC input.
 5. Efficiency is measured at rated load and 110VAC input.

Mechanical Details

